

5

Amendments in the Claims: (struck-through parts deleted and underlined parts added)

1. (currently amended) A teargas deploying device for removably mounting to a female receiver on a vehicle, said device being adapted for releasing teargas from a teargas canister and into a dwelling through a wall of the dwelling, said device

10 comprising:

an elongated tubular member having a first end and a second end, said first end being closed and having a pointed shape, said second end being open, a plurality of apertures extending into said tubular member, each of said apertures being positioned generally adjacent to said first end;

15 a canister receiving housing being fluidly coupled to said second end and

extending away therefrom, wherein a teargas canister may selectively be positioned into said housing the teargas canister may be removably positioned in said housing;

a male bracket being attached to said housing for removably mounting said

20 housing to the female receiver such that the tubular member extends away from the vehicle;

a stabilizing assembly being attached to said tubular member and said housing, said stabilizing assembly including a plurality of fins being attached to and extending along and abutting area of said tubular member and said  
housing, each of said fins radially extending outwardly from said tubular  
member and said housing; and

wherein said first end of said tubular member may be extended through a the wall such that the teargas released from the canister may enter a the dwelling bound by the wall.

30

2. (original) The device of claim 1, wherein said housing has an opening positioned opposite of said tubular member for receiving the canister, a cover being removably attached to said housing for selectively opening or closing said opening.

5           3. (original) The device of claim 1, wherein said male bracket includes a first arm and a second arm attached together at a generally perpendicular angle such that said first arm is vertically orientated and said second arm is horizontally orientated, said second arm having a free end being removably extendable into said female receiver, said first arm having an upper end attached to said housing.

10

## Claims 4 and 5 (cancelled)

15           6. (currently amended) A teargas deploying device for removably mounting to a female receiver on a vehicle, said device being adapted for releasing teargas from a  
teargas canister and into a dwelling through a wall of the dwelling, said device comprising:

20

an elongated tubular member having a first end and a second end, said first end being closed and having a pointed shape, said second end being open, a plurality of apertures extending into said tubular member, each of said apertures being positioned generally adjacent to said first end;

25

a canister receiving housing being fluidly coupled to said second end and extending away therefrom, said housing having an opening positioned opposite of said tubular member, wherein a teargas canister may selectively be positioned into said housing the teargas canister may be removably positioned in said housing, a cover being removably attached to said housing for selectively opening or closing said opening;

30

a male bracket being attached to said housing for removably mounting said housing to the female receiver such that the tubular member extends away from the vehicle, said male bracket including a first arm and a second arm attached together at a generally perpendicular angle such that said first arm is vertically orientated and said second arm is horizontally orientated, said second arm having a free end being removably extendable into said female receiver, said first arm having an upper end attached to said housing;

- 5           a stabilizing assembly being attached to said tubular member and said housing,  
          said stabilizing assembly including a plurality of fins being attached to and  
          extending along and abutting area of said tubular member and said  
          housing, each of said fins radially extending outwardly from said tubular  
          member and said housing; and
- 10          wherein said first end of said tubular member may be extended through a the wall  
          such that the teargas released from the canister may enter a the dwelling  
          bound by the wall.

Claim 7 (cancelled)

15